LARGE INDUSTRIAL POWERBOARD

ACS-63-01 63A

Designed and tested in accordance with AS/NZS61439.4

AS/NZS 61439.4 TESTED

MINING
AS/NZS3012

CONSTRUCTION
AS/NZS3012

EVENTS
AS/NZS3002

Shown with optional board stand | Registered Design No. 202014204

RDF - 1.0
max 63A under full load

What is RDF?
Click Here

AUSTRALIAN MADE

IP65

WARRANTY 5 YEAR WARRANTY

SPECIFICATIONS

Supply Inlet	63A 415V 5 pin IP67 switched CEE Form
Cascade outlet	1 x 63A 415V 5 pin IP67 switched CEE Form
Outlets	3 x 32A 415V 5 pin IP66 switched 12 x 15A 240V 3 pin IP66 auto switched
Materials	UV resistant high impact corrosion resistant V5 polyethylene
Dimensions	34kg - 55cm (L) x 55cm (W) x 69cm (H)

KEY FEATURES

Main Isolating Switch not behind a window
Lockable windows with pad lock
Breather Valve reduced condensation in board
Cascade Outlet daisy chain more boards
Three Phase Outlets with a rotary switch
Multiple RCDs reduce nuisance tripping
Entire Board is IP65 not just the outlets
Stackable Design 12 boards per pallet
Plug & Play Design no hardwiring required

POWER SAFE PRODUCTS

Certified System Quality ISO 9001 SAI GLOBAL

YOUR PARTNER IN PORTABLE POWER DISTRIBUTION

1800 338 979 | sales@powersafe.net.au
www.powersafe.net.au

Specifications subject to change without notice. July 2022.
Numerous Powersafe products are protected by either registered designs, trademarks, patents, certification or combination of IP protection.