SMALL INDUSTRIAL RANGE

Guardian 4 WAY PSOA 240V



Australian certified (AS3012, AS3190) EESS Certification No. TUV024618EA

Click Here



CONSTRUCTION















SPECIFICATIONS

| | GUHD10 10Amp | GUHD15 15Amp |
|--------------|--|--|
| Supply Inlet | 1.8m braided lead 3 pin plug 240V IP66 10Amp | 1.8m braided lead 3 pin plug 240V IP66 15Amp |
| Outlets | 4 x 10A 3 pin IP66 auto switched | 4 x 15A 3 pin IP66 auto switched |
| Materials | Injection Molded Plastic | |
| Dimensions | 2.5 kg - 22cm (L) x 24cm (W) x 26cm (H) | |



KEY FEATURES

Easy Opening sockets and outlets
Lockable windows with pad lock
Lead is braided earth screened
RCBO fitted to ensure safety and protection
Rubber Outer Skin for impact protection
Internal Lead Clamp eleviating strain on lead
Entire Board Is IP66 not just the outlets
Independently Tested certified by TUV Rheinland
Plug & Play Design no hardwiring required

YOUR PARTNER IN PORTABLE POWER DISTRIBUTION

1800 338 979 | sales@powersafe.net.au www.powersafe.net.au