

EXTENSION LEADS

Three Phase H07 RUBBER 415V

Manufactured to Australian & New Zealand
Standards AS/NZS 3123,
EN 60309-1 & EN 60309-2

✓ **CONSTRUCTION**
AS/NZS3012

✓ **MINING**
AS/NZS3012

✓ **EVENTS**
AS/NZS3002



Need Braided Leads
[Click Here](#)



SPECIFICATIONS

| | 20Amp | 32Amp | 50Amp | 63Amp |
|------------|---|------------------|-------------------|-------------------|
| Cable | 6mm ² | 6mm ² | 10mm ² | 16mm ² |
| Conductor | Fine wire tinned annealed copper | | | |
| Insulation | Inner: EPDM Rubber Outer: Chlorinated Polyethylene CPE | | | |
| Temp Range | -25°C to +90°C | | | |

KEY FEATURES

Heavy Duty UV, sunlight, oil & weather resistant
Submersible up to 500 metres
Highly Flexible industrial strength rubber cable
Built in Australia by fully qualified electricians
Plug & Socket available in 56 style or Cee Form
Standard lengths 10, 15, 20, 25 & 30 metres
Custom lengths available on request
Custom Name printed or heat shrink available



**POWER
SAFE**
PRODUCTS



YOUR PARTNER IN PORTABLE POWER DISTRIBUTION

1800 338 979 | sales@powersafe.net.au
www.powersafe.net.au

Specifications subject to change without notice. July 2022.

Numerous Powersafe products are protected by either registered designs, trademarks, patents, certification or combination of IP protection.