

MOUNTABLE POWERBOARD

WMS-03-STD 48A

Designed and tested in accordance with AS/NZS61439.4



✓ **MINING**
AS/NZS3012

✓ **CONSTRUCTION**
AS/NZS3012

✓ **EVENTS**
AS/NZS3002



Registered Design No. 202014205

RDF - 0.5
max 24A under full load

What is RDF?
[Click Here](#)



SPECIFICATIONS

Supply Inlet	Internal terminals ready for connection to MCB on generator /power supply
Alternative Supply	Connected cable
Outlets	1 x 32A 415V 5 pin IP66 switched 3 x 15A 240V 3 pin IP66 auto switched
Materials	UV resistant high impact corrosion resistant V5 polyethylene
Dimensions	15kg - 57cm (H) x 40cm (W) x 29cm (D)

KEY FEATURES

- Main Isolating Switch** not behind a window
- Lockable** hinged door & windows with pad lock
- Breather Valve** reduced condensation in board
- Three Phase Outlet** with a rotary switch
- Mounting Brackets** supplied for easy installation
- Entire Board is IP65** not just the outlets
- Ready-Made** for generators, wall mounts or portable frames.



YOUR PARTNER IN PORTABLE POWER DISTRIBUTION

1800 338 979 | sales@powersafe.net.au
www.powersafe.net.au