

THREE PHASE PSOA

RB8-5-1 32A 415V



Australian certified (AS3012, AS3190)
EESS Certification No. TUV026033EA

[Click Here](#)

✓ **CONSTRUCTION**
AS/NZS3012

✓ **MINING**
AS/NZS3012

✓ **EVENTS**
AS/NZS3002



SPECIFICATIONS

Supply Inlet	1.8m rubber flex lead with 32A 415V 5 pin IP66 plug
Outlets	1 x 32A 415V 5 pin IP66 switched outlet 5 x 15A 415V 5 pin IP66 auto switched
Materials	UV resistant high impact corrosion resistant V5 polyethylene
Dimensions	11 kg -64cm (L) x 30cm (W) x 19.5cm (H)

KEY FEATURES

- Main Isolating Switch** not behind a window
- Lockable** windows with pad lock
- Converting Three Phase** power to single phase
- Individual RCD** each outlet with own protection
- Entire Board is IP55** not just the outlets
- Built in Australia** by fully qualified electricians
- Plug & Play Design** no hardwiring required



**POWER
SAFE**
PRODUCTS



YOUR PARTNER IN PORTABLE POWER DISTRIBUTION

1800 338 979 | sales@powersafe.net.au

www.powersafe.net.au

Specifications subject to change without notice. July 2022.
Numerous Powersafe products are protected by either registered designs, trademarks, patents, certification or combination of IP protection.