

## **SMALL INDUSTRIAL RANGE**

## 4-Way PSOA The Guardian

240v Single Phase Power Board

The Guardian is the perfect entry level power board for those requiring IP66 protection with the added safety of a braided lead. The Guardian meets the requirements of mining and construction sites.



Australian certified (AS3012, AS3190) for construction sites.

Click for EESS Certification
No. TUV024618EA



## **KEY FEATURES**

- Independently tested and certified by TUV Rheinland<sup>®</sup>
- Rubber outer skin for impact protection
- Braided earth screened lead
- Window is pad lockable
- Easy opening socket outlets
- Internal strain relief on incoming lead
- Plug-and-play design no hardwiring required
- Entire board tested to IP66 for outdoor use (test report available).

| SPECIFICATIONS |  |  |  |
|----------------|--|--|--|
|                | GUHD10<br>10 Amp   | GUHD15<br>15 Amp   |  |
| Supply         | 1.8m earth screened<br>lead with 10A 240V 3 pin<br>plug IP66 | 1.8m earth screened<br>lead with 15A 240V 3 pin<br>plug IP66 |  |
| Outlets        | 4 x 10A 3 pin auto<br>switched outlets IP66                  | 4 x 15A 3 pin auto<br>switched outlet IP66                   |  |
| RCBO           | 10A 2 pole RCBO 10kA<br>30mA Type A                          | 16A 2 pole RCBO 10kA<br>30 mA Type A                         |  |
|                | T  |  |  |

| IP Rating  | IP66                                    |
|------------|---|
| Materials  | Injection Molded Plastic                |
| Dimensions | 2.5 kg - 22cm (L) x 24cm (W) x 26cm (H) |





## MADE TOUGH FOR AUSTRALIAN CONDITIONS

1800 338 979 | sales@powersafe.net.au www.powersafe.net.au



