INDUSTRIAL LIGHTING RANGE

LED floodlight **200W Slimline**

Part No. PS-FL200/56

Designed as plug-and-play temporary lighting, this slimline LED floodlight is built for outdoor use.

With a powder coated body for anti-corrosion and a toughened poly carbonate lens, this powerful light is IP65 rated.



SAA Certificate No. SAA182224

SPECIFICATIONS

Surge protected	4 KV
Output lumens	130-140 L/Watt
Watt	200W
LED driver	Mean-well driver
CCT	5000K
Input voltage	100-277 V a.c.
Impact protection	IK08
Power factor	-0.97
IP rating	IP65
Test standard	AS/NZS 60598.1:2017

IP Rating	IP65
Materials	Powder-coated aluminium / toughened polycarbonate lens
Dimensions	7.6 kg 400cm (L) x 360cm (W) x 60cm (H)



Covered by Powersafe's

> one-year warranty.

MADE TOUGH FOR AUSTRALIAN CONDITIONS

1800 338 979 | sales@powersafe.net.au www.powersafe.net.au





Specifications subject to change without notice. March 2021. Numerous Powersafe products are protected by either registered designs, trademarks, patents, certification or combination of IP protection.

KEY FEATURES

High quality 6063 aluminium body •

INGENERITI

HISHI

- Independently tested and certified
- Braided earth screened lead
- Mounting holes to enable permanent mounting •
- Internal strain relief on incoming lead
- Plug-and-play design no hardwiring required
- Cascadeable 1m to plug, 9m to socket

OPTIONAL

Scaffold mounting bracket

