

THREE PHASE PSOA

RB6-6 32A 415V



Australian certified (AS3012, AS3190) EESS
Certification No. TUV-026033-EA

[Click Here](#)

✓ **CONSTRUCTION**

AS/NZS3012

✓ **MINING**

AS/NZS3012

✓ **EVENTS**

AS/NZS3002



SPECIFICATIONS

Supply Inlet	1.8m rubber flex lead with 32A 415V 5 pin IP66 plug
Outlets	6 x 15A 415V 5 pin IP66 auto switched
Materials	UV resistant high impact corrosion resistant V5 polyethylene
Dimensions	4.5 kg - 43cm (L) x 27cm (W) x 14cm (H)

KEY FEATURES

- Lockable** windows with pad lock
- Converting Three Phase** power to single phase (each outlet supplying up to 15A at the same time)
- Paired RCD** two outlets protected per RCD
- Entire Board is IP66** not just the outlets
- Built in Australia** by fully qualified electricians
- Plug & Play Design** no hardwiring required



**POWER
SAFE**
P R O D U C T S



**YOUR PARTNER IN
PORTABLE POWER DISTRIBUTION**

1800 338 979 | sales@powersafe.net.au

www.powersafe.net.au

Specifications subject to change without notice. July 2022.
Numerous Powersafe products are protected by either registered designs, trademarks, patents, certification or combination of IP protection.