

Switched Industrial Range

240V Single Phase Plug – Type A



The RB8 is designed as a plug and play, temporary distribution board for small to medium work sites. Necessary in situations where maximum isolation protection is required; allowing the individual outlets to be padlocked in the on/off position. The use of a braided lead, 10kA 30mA RCBO and lockable window the user can rest assured that the RB range will be compliant on even the most safety conscience mining or construction site.



Manufactured from high impact and corrosion resistant polyethylene, these boards are designed for outdoor use, meeting IP66 standards (dustproof, jets of water) and come with a five-year pro rata warranty.

Suitable for all applications including invertor generators.



Fitted as standard with earth screened leads

KEY FEATURES

- Braided earth screened lead
- Outlets can be locked off at the rotary switch
- Windows are pad lockable
- All boards are built by Australian Certified electricians
- Five-year pro rata warranty
- Our entire board has been tested to IP66 not just the outlets
- Plug and go design – no hardwiring required
- Boards are made from UV resistant high impact polyethylene

SPECIFICATIONS

IP Rating:	IP66
Materials:	UV resistant high impact polyethylene
Dimensions:	8kg – 63cm (L) x 30cm (W) x 22cm (H)

	RB8-10TA 10A 4 x Outlets	RB8-15TA 15A 4 x Outlets
Supply:	1.8m earth screened lead with 10A 240V 3 pin plug IP66	1.8m earth screened lead with 15A 240V 3 pin plug IP66
Outlets	4 x 10A 2 pole 3 pin switched outlets IP66	4 x 15A 2 pole 3 pin switched outlets IP66
RCBO:	10A 2 pole RCBO 10kA 30mA Type A	16A 2 pole RCBO 10kA 30mA Type A

Specifications subject to change without notice, Version: November 2020. Numerous Powersafe products are protected by either registered designs, trademarks, patents, certification or a combination of IP protection



Made Tough for Australian Conditions

1800 338 979 | sales@powersafe.net.au

www.powersafe.net.au